

The MTN/VM220 is a compact, rechargeable, portable handheld Vibration meter designed to conform to ISO10816-3 and operate with a constant current accelerometer providing accurate vibration and temperature measurements. Features comprise of the ability to store up to 100 time-stamped readings, including; RMS, peak, peak, crest factor and bearing conditions all on an easy to read vibrant colour LCD display.

### MTN/VM220



### **Carrying case**



#### **Features**

- Rechargeable Lithium-ion battery with worldwide charger
- Switchable low pass filter
- User-selectable units
- High performance crisp colour LCD display.
- RMS, peak, peak-peak, crest factor readings in acceleration, velocity or displacement modes
- Bearing condition modes (acceleration and velocity)
- 100 memories can store vibration, temperature and time
- Tough rubberised case
- Adaptive amplifier for high accuracy
- AC output
- · Audio output for listening to vibration directly
- Supplied with MTN/2200T probe sensor, others available.

### **Specifications**

Measurement ranges	
Acceleration Velocity Displacement	200g 2000mm/s 2000 μm
Temperature	< 100°C
Modes	RMS Peak Peak-peak Crest factor Bearing acceleration Bearing velocity

## ISO10816-3

• 8 modes for machine classes I, II, III, IV, rigid/fixed foundations

**Temperature** 

• Visual indication of machine status:

Unacceptable
Unsatisfactory
Satisfactory
Good

### Frequency range


Low pass filters 5kHz, 10kHz, 20kHz
Band-pass filter 1-10kHz



#### **Dimensions**



# VM220 colour display



Units	
Acceleration Velocity Displacement Temperature	g, m/sec² mm/sec, in/sec μm, mils °C, °F
Display	
Type Resolution Viewing angle Viewable size	TFT 16bit colour 160 x 128 100° 35 x 28mm
Memory	
Size	100 slots storing vibration, time, date, temperature, filter, units
Connections	
Power/Data Headphones/AC signal Sensor	USB mini-B 3.5mm stereo 4 pin Lumberg
Environmental	
Operating temperature	0 to +45°C
Storage temperature	-20 to +60°C
Power	
Charger	100-240V/5V 1A USB with 4 adaptors
Battery	Li-ion 3.7V
Battery life	>12 hours
Power status	Battery icon indicates charging, battery level
Dimensions	
Size (L x W x H)	133 x 78 x 28mm
Accessories	
MTN/VM220 MTN/2100-X MTN/MM001 MTN/PS002	Vibration meter Probe Magnet 4" ¼"-28UNF Spike
MTN/CA476	Coiled sensor cable



# SENSORES E INSTRUMENTACION GUEMISA S.L.

MTN/CA477

MTN/BT004

MTN/HE016

MTN/HB039

C\ La Fundición 4 Bis - PI 1ª Oficina-2 28522 Rivas Vaciamadrid (Madrid) Telf. 91 764 21 00 email: <a href="mailto:ventas@guemisa.com">ventas@guemisa.com</a>



USB A to mini USB B cable

Carry case

Handbook

Worldwide adaptor with 4 adaptors