

WIND SPEED DETECTOR TUNA 20

TUNA 20 has been designed to measure wind speed and outside air temperature. High wind shield factors cool down buildings faster and with wind measurement the heating system can be compensated to take the cooling effect into account.

Linear output signal is calculated based on the cooling effect caused by the wind to the temperature measurement elements.

TUNA 20 can be configured to operate with 0...10 Vdc or 4...20 mA output options.

Using RY 1-U relay module the voltage signal can be converted to a voltagefree 230 Vac rated contact.

Installation instructions:

Sensor is mounted on a wall with the measurement element downwards.

The sensor should be mounted on a wall where the wind speed is most prevalent. The wall should continue on both sides of the sensor for a minimum of 3 meters to provide accurate measurement. The sensor should also be more than 1 m below the roof edge.



Technical data :

Supply	24 Vac/dc (22-28Vac/dc), <1,5 VA
Measurement ranges	wind speed 0...20 m/s temperature -50...50 °C
Outputs	0...10 V, < 2mA 4...20 mA, < 600 ohm
Deviation, wind speed	< 20 % of the measurement, (at 25 °C)
Deviation, temperature	< 0,5 °C (at 25 °C, > 0,2 m/s)
Operating temperature	-50...50 °C
Time constant	8s (63%)
Mounting	Wall mounting with screws
Protection class	IP 54 (transmitter)
Materials:	PBT, PC, PA plastics and painted steel

Wiring terminals:

1	supply 24 Vac/dc
2	0 V
3	output 0...10 V / 4..20mA = 0...20 m/s
4	output 0...10 V / 4..20mA = -50...50 °C

Ordering guide:

Model	Product no.	Description
TUNA 20	1136010	combined wind speed and temperature sensor

Products fulfill the requirements of directive 2004/108/EY and are in accordance with the standards EN61000-6-3: 2001 (Emission) and EN61000-6-2: 2001 (Immunity).



GUEMISA
Sta. Virgilia, 29 - 28033 Madrid - Tfno.: 91 764 21 00
Desde 1986 suministrando sensores e instrumentación
<http://www.guemisa.com> - ventas@guemisa.com

